# **Surface Degassing and the High-T Reservoir: Insights for Geothermal Exploration**

### Mark Harvey

University of Connecticut, Storrs, USA

**Keywords:** conceptual, model, exploration, CO2, flux, heat, flow, recharge

#### **ABSTRACT**

This paper summarizes results from CO<sub>2</sub> flux studies conducted in a variety of geothermal systems world-wide. Results show general relationships between the intensity of soil CO<sup>2</sup> flux, and characteristics of the underlying reservoir. In general, the magnitude of soil diffuse CO<sub>2</sub> flux at the surface can be related to topography and reservoir temperature. This general relationship can be explained by the following sequence of processes. Firstly, surface topography directs surface and subsurface recharge; all else being equal, geothermal systems located in lower elevation areas receive a greater lateral inflow of recharge. Conversely, higher elevation systems receive less recharge, and this raises reservoir temperature; higher elevation systems are generally hotter for the same reason engines run hotter when they are low on coolant. Accordingly, topography influences reservoir temperature. Secondly, temperature controls the concentration of  $CO<sub>2</sub>$  in the reservoir via temperature-dependent mineral-water equilibrium. Thirdly, reservoir  $CO_2$  content controls the magnitude of soil diffuse  $CO_2$  flux at the surface. The relationship between reservoir CO<sup>2</sup> content and temperature is the basis for a new CO<sup>2</sup> flux-based geothermometer for geothermal exploration. These findings have implications for the development of hydrothermal electricity, currently slowed by the economic risks of exploration. We have implications for the development of hydrothermal electricity, currently slowed by the econo emphasize recharge as an important factor in the science of geothermal exploration, and the utility of the CO<sub>2</sub> flux survey technique for geothermal resource evaluation. for geothermal resource evaluation.

# **1. INTRODUCTION**

A common model of a magmatic hydrothermal system consists of a convecting cell of fluid. Meteoric water exchanges heat with a A common model of a magmatic hydrothermal system consists of a convecting cell of fluid. Meteoric water exchanges heat with a magmatic body at depth then rises toward the surface through permeable rock formations as a high density water, steam and gas (mostly CO<sub>2</sub>). Rising CO<sub>2</sub> intercepts a hydrothermal reservoir and undergoes geochemical reactions (**[Figure 1](#page-0-0)**); the reservoir is a sink for CO<sub>2</sub> (CO<sub>2</sub> rising from beneath is captured as calcite), and a source of CO<sub>2</sub> (released to the (**rigure 1**); the reservoir is a sink for CO<sub>2</sub> (CO<sub>2</sub> rising from beheath is captured as calcite), and a source of CO<sub>2</sub> (released to the system is typically recharged at the margins by meteoric water (*Giggenbach*, 1995; *Dempsey et al., 2012*), or seawater in some coastal settings (*Sveinbjornsdottir et al., 1986; Parello et al., 2000; Dotsika et al.,* 2009). In many systems, magmatic water is a minor component of recharge (*Giggenbach*, 1995). For most non-marine systems, recharge is of meteoric origin. recharge is of meteoric origin.



Magmatic heat and  $CO<sub>2</sub>$  source

<span id="page-0-0"></span>**Figure 1 Simple meteoric recharged hydrothermal system conceptual model. CO<sup>2</sup> originates from the magmatic heat source (intrusive), then rises toward the surface before encountering a hydrothermal reservoir. Note: the flow of CO<sup>2</sup> from the intrusive may not be not the same as that measured at the surface; the reservoir is a source or sink for CO2.**

CO<sup>2</sup> flux surveys in geothermal and volcanic areas have been increasing in number since equipment became commercially available in the late 1990's. Accordingly, the past 15-20 years can be regarded as the pioneer phase of geothermal CO<sub>2</sub> flux exploration, with a small but growing body of literature. Understandably, most early studies have made "stand-alone" interpretations relating solely to the area under investigation (e.g. fault permeability, heat flow, CO<sup>2</sup> flow) (e.g. *Chiodini et al.*, 1996; *Werner et al.*, 2000; *Fridriksson et al.*, 2006), with only limited comparison to other systems; there simply were not enough published studies for comparison.

The lack of comparative studies leaves fundamental unanswered questions, which are addressed by this paper. For example, when we compare the intensity of CO<sup>2</sup> flux for a variety geothermal system, do we observe a systematic relationship to topography, and water recharge mechanisms? Alternatively, when we examine a variety of well understood (i.e. drilled) geothermal systems do we see a relationship between surface  $CO<sub>2</sub>$  flux intensity, reservoir gas content and temperature? This paper summarizes recent investigations into the controls over CO<sup>2</sup> flux intensity in thermal areas, which have improved the predictive power of CO<sup>2</sup> flux to reveal the nature of the deep reservoir in undrilled geothermal systems.

#### **2. SURFACE CO<sup>2</sup> FLUX AND RECHARGE TO THE RESERVOIR**

Here we summarize the findings of *Harvey et al.* (2015), which determined that variations in surface fluxes of CO<sub>2</sub> and heat, measured in a range of hydrothermal systems, may be explained by the specific hydrological settings of the systems (**[Figure](#page-1-0) 2**). Previous studies had observed that heat fluxes, for a variety of similar systems in the Taupo Volcanic Zone (TVZ), fall within a single order-of-magnitude (e.g. *Weir,* 2009). Further, that this range is restricted relative to the much wider range of permeabilities known to exist in reservoir host rocks (permeabilities extend over several orders of magnitude); if permeability were the primary control over system heat output, then heat fluxes would also be expected to span several orders of magnitude, but this was not observed (*Weir,* 2009).

Heat flows from geothermal systems in the TVZ were compared in previous studies (*Weir,* 2009; *Dempsey et al.,* 2012), and shown to be proportional to rainfall catchment areas estimated from modelling. These studies did not consider surface topography/watershed basins but acknowledged this will have a strong effect. For example, surface topography will affect the direction and magnitude of surface and subsurface recharge; all else being equal, geothermal systems located in lower elevation areas, or those located nearby a body of water, would receive a greater lateral inflow of recharge than systems located beneath a topographic high (e.g. volcanic cone)(**[Figure](#page-1-0) 2**). It follows that systems located in a basin, or topographic depression, should receive a greater flow of water, which is the medium of convective heat flow. All else being equal, a greater flow of water would also result in a lower reservoir temperature, which affects surface  $CO<sub>2</sub>$  flux (Section 3).

This concept is nicely illustrated in the TVZ, where it is apparent the majority of systems are located on the Waikato River (9 out of 13)(**[Figure 3](#page-2-0)**). The Waikato River constitutes the primary hydrological drainage and topographic low for the TVZ. Another example that illustrates this concept, is the generally low power density (electrical capacity per unit area of reservoir) observed for vapour dominated reservoirs. The low power density of the Geysers (USA), and Lardarello (Italy), relative to other geothermal electric plants, was noted previously and attributed to restricted recharge (Allis, 2000). Generation at these, and most other geothermal power plants (both vapour and liquid dominated), is now typically supported by artificial recharge (reinjection) of fluids into the margins of the productive reservoir (*Stefansson*, 1997; *Kaya et al.*, 2007).



<span id="page-1-0"></span>**Figure 2 Surface fluxes of CO<sup>2</sup> and H2O may be explained by the hydrological setting of the system. In the above example, topography controls recharge (note: lower-elevation reservoir is much larger), which controls surface flux of H2O and CO2.** 



# <span id="page-2-0"></span>**Figure 3 Location of hydrothermal fields (red areas) in the Taupo Volcanic Zone overlaid on a satellite digital terrain model (WGS84). Darker shading indicates lower elevation topography. Field boundaries are based on shallow electrical resistivity data (Bibby** *et al.***, 1995).**

A review of 53 geothermal fields worldwide study gave a mean power capacity of 16.2 MW electric km-2 (*Wilmarth and Stimac,*  2014). By assuming a typical conversion efficiency of 10% from thermal energy to electric (*Ghoniem,* 2011; *Zarrouk and Moon,*  2014), 16.2 MW electric  $km^2$  gives 162 MW  $km^2$ . This heat flux is comparable to the mean heat flux for meteoric supplied hydrothermal systems determined by surface CO<sub>2</sub> flux measurements in areas of thermal ground (198 MW km<sup>-2</sup>) (*Harvey et al.*, 2015). It is worth noting these values are of the same order-of-magnitude as the global average solar heat flux captured by the Earth's surface water (solar evaporation = 80 MW km<sup>-2</sup>)(*Trenberth et al., 2009*). Because the system is in a steady state, this energy is subsequently released as the evaporated moisture condenses (rain).

The energy flux associated with a phase change in water (i.e. liquid to vapour, or vice versa) is related to a change in the specific enthalpy of the fluid. This allows heat flux (e.g. MW  $km<sup>-2</sup>$ ) and water flux (e.g. tons  $km<sup>-2</sup>$  day<sup>-1</sup>) to be used interchangeably. It is important to note that such enthalpy changes are quite insensitive to temperature. For example, the change in enthalpy associated with steam (100 $^{\circ}$ C) condensation to liquid water (12 $^{\circ}$ C) in hydrothermal areas (2624 kJ kg<sup>-1</sup>), is very close to the value associated with the evaporation of Earth's surface waters  $(\sim 2260 \text{ kJ kg}^{-1})$ . Therefore, the mean heat flux for natural-state meteorically supplied geothermal systems  $(198 \text{ MW km}^2)$  may be constrained by the available incoming solar energy flux, the ultimate power source that drives the Earth's hydrological cycle.

# **3. CO<sup>2</sup> FLUX AND RESERVOIR TEMPERATURE**

Here we summarize the findings of *Harvey et al.* (2017), which explored the relationship between heat flux, CO<sub>2</sub> flux, and deep reservoir temperature for eight hydrothermal systems, located in New Zealand (6), Iceland (1) and Argentina (1). In that study, a new geothermometer for geothermal exploration (Tco<sub>2 Flux</sub>) was proposed based on soil diffuse CO<sub>2</sub> flux and shallow temperature measurements, which may be generally applied in areas of steam heated ground.

Temperature estimates derived from  $T_{CO2$   $Flux}$  were compared to reservoir temperatures (measured and inferred) from the eight areas. T $_{CO2}$  Flux temperatures were found to be close to the known (or inferred) reservoir temperatures for all eight systems. It is proposed that T<sub>CO2 Flux</sub> provides a temperature estimate that is not subject to problems of limited sample size, one of the main limitations of water and gas geothermometers.

Tco<sub>2 Flux</sub> results from some systems (Wairakei, Ohaaki, Rotokawa) indicated thermal areas receive vapour from separate aquifers. The areas of maximum  $T_{CO2}$  Flux at Wairakei and Rotokawa occur at the location of upflows (as shown in existing conceptual models). At White Island, powerful magmatic  $CO<sub>2</sub>$  flows would be expected to penetrate or bypass the acidic liquid reservoir, especially during non-equilibrium eruptive events. Such a physical process would invalidate the  $T_{CO2\text{ Flux}}$  geothermometer, which assumes temperature dependent water mineral equilibrium in neutral pH reservoir fluids.

*Harvey et al.* (2015) showed the intensity of surface CO<sub>2</sub> degassing is related to recharge but did not provide the precise mechanism through which deep recharge could influence surface CO<sup>2</sup> flux (Section 2). *Harvey et al.* (2017) proposed the mechanism, that recharge has an influence on the temperature of hydrothermal reservoirs. This provides the missing link between recharge and soil  $CO<sub>2</sub>$  flux; reservoir temperature controls the concentration of  $CO<sub>2</sub>$  in the reservoir via mineral-water equilibrium, which in turn controls the magnitude of soil diffuse CO<sup>2</sup> flux at the surface (**[Figure](#page-1-0) 2**).

The relationship between reservoir temperature and recharge is intuitive if one considers the following analogy. Here, a hydrothermal system is represented by a gasoline engine in which the engine block (reservoir rock) exchanges heat with a circulating coolant (reservoir water). A thermostat regulates temperature by regulating the flow of coolant through the block. In doing so, the coolant's temperature is also modified. A radiator with a puncture, or blown head gasket (hot spring), allows water to escape the system. If fluid is not added to the radiator (recharged) with sufficiently regularity, the block will dry, and result in a higher system temperature.

# **4.0 CONCLUSIONS**

Variations in CO<sup>2</sup> flux and reservoir temperature may be explained by topographic and hydrological factors. Recharge availability, often related to topography, exerts a strong control over the location of hydrothermal systems. Natural state heat flux for meteorically supplied geothermal systems may be constrained by the available incoming solar energy flux, the ultimate power source that drives the Earth's hydrological cycle.

Recharge also has an influence on the temperature of hydrothermal reservoirs; higher recharge flux lowers reservoir temperature, a system analogous to water-cooled gasoline engines. Thus, recharge influences reservoir temperature, which controls the concentration of reservoir CO<sup>2</sup> via temperature-dependant mineral-water equilibrium. This in turn controls the magnitude of soil diffuse CO<sub>2</sub> flux at the surface, which is the basis for a new CO<sub>2</sub> flux-based geothermometer for geothermal exploration.

These findings have implications for the development of hydrothermal electricity, currently slowed by the economic risks of exploration. We emphasize recharge as an important factor in the science of geothermal exploration, and the utility of the CO2 flux survey technique as an easily applied geothermometer.

#### **REFERENCES**

- Allis, R. (2000). Insights on the formation of vapor-dominated geothermal systems. *Proceedings of the World Geothermal Congress.* Kyushu - Tohoku, Japan, 2000.
- Chiodini, G., F. Frondini, and Raco, B. (1996). Diffuse emission of CO<sup>2</sup> from the Fossa crater, Vulcano Island (Italy). *Bulletin of Volcanology*, **58**, 41-50.
- Dempsey, D., S. Simmons, R. Archer, and Rowland, J. (2012). Delineation of catchment zones of geothermal systems in large‐scale rifted settings. *Journal of Geophysical Research: Solid Earth,* **117**.
- Dotsika, E., D. Poutoukis, J. Michelot, and Raco, B. (2009). Natural tracers for identifying the origin of the thermal fluids emerging along the Aegean Volcanic arc (Greece): Evidence of Arc-Type Magmatic Water (ATMW) participation*. Journal of Volcanology and Geothermal Research,* **179**, 19-32.
- Fridriksson, T., Kristjánsson, B. R., Ármannsson, H., Margrétardóttir, E., Ólafsdóttir, S., and Chiodini, G. (2006). CO<sup>2</sup> emissions and heat flow through soil, fumaroles, and steam heated mud pools at the Reykjanes geothermal area, SW Iceland. *Applied Geochemistry*, **21**, 1551-1569.
- Ghoniem, A. F. (2011). Needs, resources and climate change: clean and efficient conversion technologies*. Progress in Energy and Combustion Science,* **37**, 15-51.
- Giggenbach, W. F. (1995). Variations in the chemical and isotopic composition of fluids discharged from the Taupo Volcanic Zone, New Zealand*, Journal of Volcanology and Geothermal Research,* **68**, 89-116.
- Harvey, M. C., Rowland, J. V., Chiodini, G., Rissmann, C. F., Bloomberg, S., Hernández, P. A., Mazot, A., Viveiros, F., and Werner, C. (2015). Heat flux from magmatic hydrothermal systems related to availability of fluid recharge. *Journal of Volcanology and Geothermal Research*, **302**, 225-236.
- Harvey, M. C., Rowland, J. V., Chiodini, G., Rissmann, C. F., Bloomberg, S., Fridriksson, T., & Oladottir, A. A. (2017). CO2 flux geothermometer for geothermal exploration. *Geochimica et Cosmochimica Acta*, *213*, 1-16.
- Kaya, E., Zarrouk, S. J., and O'Sullivan, M. J. (2011). Reinjection in geothermal fields: a review of worldwide experience. *Renewable and sustainable energy reviews*, **15**, 47-68.
- Parello, F., Allard, P., D'Alessandro, W., Federico, C., Jean-Baptiste, P. and Catani, O. (2000). Isotope geochemistry of Pantelleria volcanic fluids, Sicily Channel rift: a mantle volatile end-member for volcanism in southern Europe*. Earth Planetary Science Letters,* **180**, 325-339.
- Stefansson, V. (1997). Geothermal reinjection experience*, Geothermics,* **26**, 99-139.
- Sveinbjornsdottir, A.E., Coleman, M.L. and Yardley, B.W.D. (1986). Origin and history of hydrothermal fluids of the Reykjanes and Krafla geothermal fields, Iceland*. Contributions to Mineralogy and Petrology,* **94**, 99-109.
- Trenberth, K.E., Fasullo, J.T., and Kiehl, J. (2009). Earth's global energy budget. *Bulletin of the American Meteorological Society,*  **90**, *311-323*.
- Weir, G. J. (2009). A mathematical model of rainfall-controlled geothermal fields*. Transport Porous Media,* **77**, 323-334.
- Werner, C., Brantley, S.L. and Boomer, K. (2000). CO<sub>2</sub> emissions related to the Yellowstone volcanic system: 2. Statistical sampling, total degassing, and transport mechanisms. *Journal of Geophysical Research: Solid Earth,* **105**, 10831-10846.
- Wilmarth, M. and Stimac, J. (2014). Worldwide Power Density Review*.* In *Proceedings 39th Workshop on Geothermal Reservoir Engineering*.
- Zarrouk, S. J. and Moon, H. (2014). Efficiency of geothermal power plants: A worldwide review*. Geothermics,* **51**, 142-153.